Material
75 FKM 181327
green

revision index	revision date		
5	9/22/2016	page	1 / 2

Physical properties	nominal range	typical values	
Density DIN EN ISO 1183-1	2.04 ±0.03	2.05	g/cm³
Hardness DIN ISO 7619-1	75 ±5	72	Shore
Rebound resilience DIN 53512	---	6	%
Modulus 100 %, DIN 53504, S2	> 6	8	MPa
Tensile strength DIN 53504, S2	> 12	14.5	MPa
Elongation at break DIN 53504, S2	> 150	220	%
Compression set DIN ISO 815, B, 22 h, 175 °C	< 15	8	%
Compression set DIN ISO 815, B, 22 h, 175 °C, in der Prüfkammer abgekühlt	< 30	16	%
Low Temperature ISO 11357-2, DSC	---	-17	°C

Temperature range -20°C to 200°C

Declarations of conformity

	Country	Part	Remark	Expires	unlimited
RoHS conform			including EU 2011/65 and EU2015/863 (ROHS III)		☑

Freudenberg
Freudenberg FST GmbH
Global Material Technology
Wolfgang Becker
Telefon: +49 (0)6201/80-2893
Fax: +49 (0)6201/88-2893
Email: wolfgang.becker@FST.com

Material
75 FKM 181327
green

revision index	revision date		
5	9/22/2016	**page**	2 / 2

No ASTM D2000 properties available

The given values are based on a limited number of tests on standard test pieces (2mm sheets) produced in the laboratory. The data from finished parts can deviate from above values depending on the manufactories process and the component geometry.

The data represents our present empirical values. It is incumbent on the person placing the order to examine whether it is suitable for its intended purpose, before using the product. All questions regarding the guarantee of this product are in line with our terms and conditions, inasmuch as statutory provisons do not plan for something else.

Freudenberg

Freudenberg FST GmbH
Global Material Technology
Wolfgang Becker
Telefon: +49 (0)6201/80-2893
Fax: +49 (0)6201/88-2893
Email: wolfgang.becker@FST.com